

Battery System Designed For Big PV Household Application

# Battery Series SMILE5-BAT



## ✓ Key Features



Modular




Plug & play



Safety



Long lifespan



### CHEMISTRY

#### AlphaESS only goes with LFP for safest operation and longest cycle-life

Whilst Alpha's batteries are slightly larger per physical capacity versus other types of Li-Ion used in electronics and EVs, they are easily banked in parallel close together because they don't suffer heat issues and thermal runaway. We have chosen LiFePO<sub>4</sub> for their superior life, safety and environmental performance.

### About AlphaESS

As one of the earliest pioneers in energy storage market with lithium iron technology, AlphaESS has a vision to pave the path for everyone in the world to enjoy clean energy one day.

We are a multinational company that currently has more than 10'000 residential and commercial systems running in 30 countries globally and our products are accredited by IEC, TÜV, CEC and many other international standards.

All AlphaESS energy systems are integrated with smart energy management solutions. AlphaESS is committed to revolutionize the future energy network through our patented German technologies.



Official Website



Scan to download APP (iOS/Android)



Twitter



FaceBook

Physical	
Model	SMILE5-BAT
Battery Type	LiFePO4 (LFP)
Battery Manufacturer	
System Weight	65kg
Dimension (W x D x H)	600mm x 250mm x 600mm
IP Protection	IP21/IP65 (Optional)
Warranty	5 Year Product Warranty, 10 Year Performance Warranty
Electrical	
Energy Capacity	5.7kWh
Usable Capacity	5.2kWh
DOD	90%
Nominal Voltage	51.2V
Operation Voltage Range	48 - 57.6V
Internal Resistance	≤30mΩ
Cycle Life	≥6000
Operation	
Max. Charge Current	56A (0.5C)
Max. Discharge Current	56A (0.5C)
Operating Temperature Range	-10°C - 50°C*
Humidity	15% - 85%
BMS	
Power Consumption	<2W (Work), <100mW (Sleep)
Monitoring Parameters	System voltage, current, cell voltage, cell temperature, PCBA temperature measurement.
SOC	Intelligent algorithm
Communication	CAN and RS485 compatible

\*When the temperature is below 0°C or above 40°C, the performance will be limited.

